



## NEROLAC EXCEL MICA MARBLE STRETCH AND SHEEN

# NEROLAC

Colours that Care



Pack shot is for creative visualization and might differ from the actual pack

### PRODUCT DESCRIPTION

KNP Nerolac Excel Mica Marble Stretch and Sheen is an extremely durable water based high performance exterior paint developed with a unique stretchable film technology, which allows it to cover hairline cracks, with a 6 year performance warranty.

### PERFORMANCE FEATURES & BENEFITS

 <p>2x Stretchability</p>	 <p>Excellent Dirt pick up resistance</p>
 <p>Crack-bridging ability</p>	 <p>6 Year performance warranty</p>
 <p>Superior Sheen Finish</p>	

Disclaimer - Refer product warranty booklet.

### APPLICATION

Thin 1 L paint with maximum 400 ml of clean water. Apply 2 to 3 coats with an Interval of 4-6 h. by brush or roller. Dark shade may require additional coat for hiding.

For horizontal surface and Parapet tops application of 3 coats is recommended for better protection.

### RECOMMENDED USAGE

Recommended for exterior of houses, architectural and commercial buildings, where high standard of surface protection is needed.

### RECOMMENDED SYSTEM FOR APPLICATION:

1. Nerolac Exterior Primer (1 coat)<sup>#</sup> Dry 4-6 h
2. Excel Mica Marble Stretch and Sheen (1<sup>st</sup> coat) Dry 4-6 h
3. Excel Mica Marble Stretch and Sheen (2<sup>nd</sup> coat) Dry 4-6 h

<sup>#</sup>Nerolac Exterior Primer, Excel Alkali Primer or self-priming of Emulsion of Excel Mica Marble Stretch and Sheen (100%thinning).

### PRECAUTIONS

1. Refer MSDS of Nerolac Excel Anti Peel Exterior Acrylic Emulsion for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition & fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection is dangerous. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 hours of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal strainers. Stir well before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment like rubber or polythene gloves, safety goggles/glasses & face mask.

## TECHNICAL DATA



\*\*\* Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.

\$: Paint with VOC in the range of 5 g/l without addition of colourants.( Ref: KNPL Lab results),VOC content may vary from batch to batch,h to batch.

\* As compared to normal cement paint. Applicable on certain shades only.

## POST APPLICATION INSTRUCTIONS

For the best performance of paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of six months.



### SAFETY FEATURES

Non-Flammable.



### PACK SIZE

1 L, 4 L, 10 L & 20 L.



### SHADE RANGE

As per Colour Scapes Fandek and shade card



### NO. OF SHADES POSSIBLE

More than 1400

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.